is the name kyle in the bible

windows - Current date in the file name - Server Fault

I have scheduled backup script that makes the database dump. How can I add the date timestamp to the file name? I am talking about Windows and CMD.

Difference between DHCP options 'Domain-Name' and 'Domain-Search'

The domain-name option specifies the client's domain name (of which there can only be one), and is specified in resolv.conf with the domain keyword. This is the domain which will be used when running hostname -f on the client. The domain-search option specifies a list of domains to use when looking up bare hostnames, and is specified in resolv.conf with the search keyword. If this option isn't ...

User principal name vs SAM account name - Server Fault

I am confused between the user principal name (UPN) and SAM account name (SAM). Heres what i know SAM- Pre-windows name, for backward compatibility with Windows NT machines etc. DOMAIN/USERA, look...

windows - Resolve host name from IP address - Server Fault

I'm looking for a command line tool which gets an IP address and returns the host name, for Windows.

Definition of Fully qualified domain name - Server Fault

To be less than fully qualified means that the name you're looking at only makes sense within the context of a search-list or default-domain. RFC 1535 was interesting because a lot of us had up until that time used multi-label local names and still expected search-list behaviour -- and this broke too many other things, so was outlawed.

How do registrars register authoritative name servers with root name ...

How do top-level root name servers authenticate queries from registrars to change authoritative name servers for a given domain? Is that even public knowledge? For example, say you own example.com. You want to change the authoritative name servers for it. You give your registrar the addresses of the new name servers. So far, so good.

Can someone please explain Windows Service Principle Names (SPNs ...

A Service Principal Name is a concept from Kerberos. It's an identifier for a particular service offered by a particular host within an authentication domain. The common form for SPNs is service class / fqdn @ REALM (e.g. IMAP/ mail.example.com@EXAMPLE.COM). There are also User Principal Names which identify users, in form of user @ REALM (or user1 / user2 @ REALM, which identifies a speaks ...

Active Directory Domain where FQDN and NetBIOS name are the same

2 I have "inherited" an ancient domain (NT4, then upgraded to Win2000 Mixed Mode and now running on Win2003) where the NetBIOS name coincides with the DNS/FQDN one, and this is giving us problems with remote clients which need to be joined to the domain.

linux - ps show column name - Server Fault

ps show column name Ask Question Asked 10 years, 10 months ago Modified 3 years, 4 months ago

How can I configure my DNS settings on Debian 12?

I'm trying to change my DNS settings on my Debian 12 VPS, and by this I mean, I want to use a public resolver like 1.1.1.1 instead of my VPS host's resolver. I remember in Debian 11 I could just ed...