

the function requires that management evaluate operations against some norm

AI generated article from Bing

javascript - What does \$(function() {}); do? - Stack Overflow

A function of that nature can be called at any time, anywhere. jQuery (a library built on Javascript) has built in functions that generally required the DOM to be fully rendered before being called.

iife - What is the (function() {}) () construct in JavaScript ...

Correction suggested by Guffa: The function is executed right after it's created, not after it is parsed. The entire script block is parsed before any code in it is executed. Also, parsing code doesn't automatically mean that it's executed, if for example the IIFE is inside a function then it won't be executed until the function is called.

What's the difference between __PRETTY_FUNCTION__, __FUNCTION__, __func__?

About `__func__`: "The identifier `__func__` is implicitly declared by the translator as if, immediately following the opening brace of each function definition, the declaration: `static const char __func__[] = "function-name";` appeared, where `function-name` is the name of the lexically-enclosing function. This name is the unadorned name of the ...

What is "function*" in JavaScript? - Stack Overflow

12 The `function*` type looks like it acts as a generator function for processes that can be iterated. C# has a feature like this using "yield return" see 1 and see 2 Essentially this returns each value one by one to whatever is iterating this function, which is why their use case shows it in a foreach style loop.

What is the purpose of a self executing function in javascript?

509 It's all about variable scoping. Variables declared in the self executing function are, by default, only available to code within the self executing function. This allows code to be written without concern of how variables are named in other blocks of JavaScript code. For example, as mentioned in a comment by Alexander:

syntax - What does %>% function mean in R? - Stack Overflow

I have seen the use of %>% (percent greater than percent) function in some packages like dplyr and rvest. What does it mean? Is it a way to write closure blocks in R?

What does the exclamation mark do before the function?

`(function(){})(!)`; Lastly, `!` makes the expression return a boolean based on the return value of the function. Usually, an immediately invoked function expression (IIFE) doesn't explicitly return anything, so its return value will be undefined, which leaves us with `!undefined` which is true. This boolean isn't used.

How do function pointers in C work? - Stack Overflow

358 Function pointers in C can be used to perform object-oriented programming in C. For example, the following lines is written in C:

Functions that return a function: what is the difference between ...

Calling the function with `()` in a return statement executes the function, and returns whatever value was returned by the function. It is similar to calling `var x = b();`, but instead of assigning the return value of `b()` you are returning it from the calling function `a()`.

What does (function(\$ {})(jQuery); mean? - Stack Overflow

`(function(doc){ doc.location = '/'; })(document);`//This is passed into the function above As for the other questions about the plugins: Type 1: This is not a actually a plugin, it's an object passed as a function, as plugins tend to be functions. Type 2: This is again not a plugin as it does not extend the `$.fn` object. It's just an extension of the jQuery core, although the outcome is the ...