

triangulo de las bermudas mapa

AI generated article from Bing

Triângulo - Hardwood Flooring

We are an industry focused on quality and sustainability of Brazilian hardwood. Check out our hardwood collections recognized around the world by builders, interior designers, architects and residential consumers.

Engineered - Triângulo

TRIÂNGULO® utilizes the highest quality engineering process in the industry.

Solids - Triângulo

The Triangulo crystal clear pre-finishing process applies as many as 9 coats of Aluminum Oxide for maximum durability and enhanced beauty. Like our thick-sawn engineered products, the principal advantage of solid wood flooring is its ability to be re-sanded and refinished over many many years.

Floors - Triângulo

Rated 2.53 out of 5 Compare with another product

About us - Triângulo

Triangulo Hardwood Flooring has been dedicated to the manufacturing of hardwood products since 1972. This family-owned business in Brazil has been globally recognized for sustainability, innovative products and cutting edge technology.

Tigerwood - Triângulo

Adherence - At least 3 B (as standard norm ASTM D 3359 - 02); Glue Bond (ANSI/HPVA EF 2002); Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2); Total VOC (CA Specification 01350) - ≤ 0.5 mg/m³; Critical radiant flux (Class 1) - 0,45watts/cm² (ASTM E648)

Contact - Triângulo

CONTACT +1 (757) 420 4771 +1 (757) 420 4772 FAX: 757-280-3040 sales@triangulo.us Office Hours: Monday - Friday 8:00 AM - 5:00 PM (Eastern time) SUBSCRIBE TO OUR NEWSLETTER News, inspirations and digital materials. Nome

Brazilian Pecan - Triângulo

Adherence - At least 3 B (as standard norm ASTM D 3359 - 02); Glue Bond (ANSI/HPVA EF 2002); Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2); Total VOC (CA Specification 01350) - ≤ 0.5 mg/m³; Critical radiant flux (Class 1) - 0,45watts/cm² (ASTM E648)

Brazilian Cherry E.Wide - Triângulo

Adherence - At least 3 B (as standard norm ASTM D 3359 - 02); Glue Bond (ANSI/HPVA EF 2002); Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2); Total VOC (CA Specification 01350) - ≤ 0.5 mg/m³; Critical radiant fluxe (Class 1) - 0,45watts/cm² (ASTM E648)

Nordic - Triângulo

Our Nordic Collection draws on a unique Brazilian oak species. The movement within will capture your eyes and your imagination. Sharing pathways of unbending woodgrain to subtle contours reminiscent of a gently curving shoreline.